


Feeler Gauges

Series 184 - Feeler Gauge


This feeler gauge is ideal for a variety of measuring tasks and offers you the following benefits:

- Size clearly stamped on each leaf
- Leaves are easy to remove and can be individually locked open.

Metric					
No.	Range	Accuracy	Number of leaves	Leaf length [mm]	Mass [g]
184-301S	0,05-0,3 mm by 0,05 mm, 0,4-1 mm by 0,1 mm	0,03-0,15 mm: ±0,005 mm, 0,2- 0,5 mm: ±0,012 mm, 0,55-1 mm: ±0,02 mm	13	150	121
184-302S	0,03-0,1 mm by 0,01 mm, 0,2-0,5 mm by 0,1 mm, 0,15 mm	0,03-0,15 mm: ±0,005 mm, 0,2- 0,5 mm: ±0,012 mm, 0,55-1 mm: ±0,02 mm	13	150	67
184-303S	0,05-0,15 mm by 0,01 mm, 0,2-1 mm by 0,05 mm	0,03-0,15 mm: ±0,005 mm, 0,2- 0,5 mm: ±0,012 mm, 0,55-1 mm: ±0,02 mm	28	150	195
184-304S	0,05-1 mm by 0,05 mm	0,03-0,15 mm: ±0,005 mm, 0,2- 0,5 mm: ±0,012 mm, 0,55-1 mm: ±0,02 mm	20	150	184
184-305S	0,05-0,3 mm by 0,05 mm, 0,4-1 mm by 0,1 mm	0,03-0,15 mm: ±0,005 mm, 0,2- 0,5 mm: ±0,012 mm, 0,55-1 mm: ±0,02 mm	13	100	82
184-306S	0,05-0,2 mm by 0,05 mm, 0,3-0,8 mm by 0,1 mm	0,03-0,15 mm: ±0,005 mm, 0,2- 0,5 mm: ±0,012 mm, 0,55-1 mm: ±0,02 mm	10	100	62
184-307S	0,03-0,1 mm by 0,01 mm, 0,2-0,5 mm by 0,1 mm, 0,15 mm	0,03-0,15 mm: ±0,005 mm, 0,2- 0,5 mm: ±0,012 mm, 0,55-1 mm: ±0,02 mm	13	100	47
184-308S	0,05-0,2 mm by 0,05 mm, 0,3-0,8 mm by 0,1 mm	0,03-0,15 mm: ±0,005 mm, 0,2- 0,5 mm: ±0,012 mm, 0,55-1 mm: ±0,02 mm	10	150	91
184-313S	0,05-0,15 mm by 0,01 mm, 0,2-1 mm by 0,05 mm	0,03-0,15 mm: ±0,005 mm, 0,2- 0,5 mm: ±0,012 mm, 0,55-1 mm: ±0,02 mm	28	100	129



184-303S



184-304S



184-308S

Knife Edge Straight Edge

Series 528

This Knife Edge Straight Edge offers you the following benefits:

- Its straight edges are especially suited to testing the flatness of surfaces.
- It has a hardened, ground and micro lapped measuring edge.



Series 528

No.	Cross section	Section	Accuracy	Length [mm]	Mass [g]
528-100	25 x 6 mm	60°	DIN 874-2	50	40
528-101	25 x 6 mm	60°	DIN 874-2	75	50
528-102	25 x 6 mm	60°	DIN 874-2	100	60
528-110	25 x 6 mm	60°	DIN 874-2	125	80
528-103	25 x 6 mm	60°	DIN 874-2	150	100
528-104	25 x 6 mm	60°	DIN 874-2	200	190
528-105	32 x 7 mm	60°	DIN 874-2	300	370
528-106	40 x 8 mm	60°	DIN 874-2	400	1080
528-107	50 x 10 mm	60°	DIN 874-2	500	1400