

Setting Rings

Metric Steel

No.	Nominal size ød [mm]	Type	D [mm]	E [mm]	T [mm]	Tolerance nominal size / marked diameter [µm]	Uncertainty of marked diameter [µm]	Roundness / Cylindricity [µm]	H [mm]	Warranted calibration surface K [mm]
177-220	1	A	20		4	±10	1,5	1	1.6	0.8
177-222	1,1	A	20		4	±10	1,5	1	1.6	0.8
177-225	1,2	A	20		4	±10	1,5	1	1.6	0.8
177-227	1,3	A	20		4	±10	1,5	1	1.6	0.8
177-230	1,4	A	20		4	±10	1,5	1	1.6	0.8
177-236	1,75	A	25		5	±10	1,5	1	1.6	1.8
177-239	2	A	25		5	±10	1,5	1	1.6	1.8
177-242	2,25	A	25		5	±10	1,5	1	1.6	1.8
177-208	2,5	A	25		7	±10	1,5	1	1.7	3.6
177-246	2,75	A	25		7	±10	1,5	1	1.7	3.6
177-248	3	A	25		7	±10	1,5	1	1.7	3.6
177-250	3,25	A	25		7	±10	1,5	1	1.7	3.6
177-252	3,5	A	25		7	±10	1,5	1	1.7	3.6
177-255	3,75	A	25		7	±10	1,5	1	1.7	3.6
177-204	4	A	25		7	±10	1,5	1	1.7	3.6
177-257	4,5	A	25		7	±10	1,5	1	1.7	3.6
177-205	5	A	25		7	±10	1,5	1	1.7	3.6
177-263	5,5	A	25		7	±10	1,5	1	1.7	3.6
177-267	6	A	25		7	±10	1,5	1	1.7	3.6
177-271	6,5	A	25		7	±10	1,5	1	1.7	3.6
177-275	7	A	25		7	±10	1,5	1	1.7	3.6
177-125	8	A	32		10	±10	1,5	1	2.0	6.0
177-279	9	A	32		10	±10	1,5	1	2.0	6.0
177-126	10	A	32		10	±10	1,5	1	2.0	6.0
177-284	12	A	32		10	±10	1,5	1	2.0	6.0
177-132	14	A	38		10	±10	1,5	1	2.0	6.0
177-177	16	A	45		10	±10	1,5	1	2.0	6.0
177-133	17	A	45		10	±10	1,5	1	2.0	6.0
177-285	18	A	45		10	±10	1,5	1	2.0	6.0
177-286	20	A	45		10	±10	1,5	1	2.0	6.0
177-139	25	A	53		15	±10	1,5	1	3.2	8.6
177-288	30	A	71		15	±10	1,5	1	3.2	8.6
177-140	35	A	71		15	±10	1,5	1	3.2	8.6
177-290	40	A	71		15	±10	1,5	1	3.2	8.6
177-178	45	A	85		15	±10	1,5	1	3.7	7.6
177-146	50	A	85		20	±20	1,5	1	3.7	12.6
177-292	60	A	112		20	±20	1,5	1	3.7	12.6
177-314	62	A	112		20	±20	1,5	1,5	3.7	12.6
177-147	70	A	112		20	±20	1,5	1,5	3.7	12.6
177-316	75	A	125		25	±20	1,5	1,5	4.2	16.6
177-294	80	A	125		25	±20	1,5	1,5	4.2	16.6
177-318	87	A	140		25	±20	1,5	1,5	4.2	16.6
177-148	90	A	140		25	±20	1,5	1,5	4.2	16.6
177-296	100	A	160		25	±20	1,5	2	4.2	16.6
177-298	125	B	210	168	38,1	±20	2,5	2	5.3	27.5
177-300	150	B	235	187	38,1	±20	2,5	2	5.3	27.5
177-302	175	B	260	215	38,1	±20	2,5	2,5	5.3	27.5
177-304	200	B	311	244	38,1	±20	2,5	2,5	5.3	27.5
177-306	225	B	337	264	38,1	±20	2,5	2,5	5.3	27.5
177-308	250	B	362	290	38,1	±20	2,5	3	5.3	27.5
177-310	275	B	413	321	38,1	±20	2,5	3	5.3	27.5
177-312	300	B	438	340	38,1	±20	2,5	3	5.3	27.5